

REMOTE HORN

MODEL RH

GENERAL DESCRIPTION:

Toxalert International's Model RH, shown at right, is used in conjunction with Toxalert International gas detection systems and provides excellent audible indication if warning or alarm conditions exist. These horns are available in four voltages – 12 VDC, 24 VDC, 24 VAC and 120 VAC.

Toxalert Model RH horns are designed for both indoor and outdoor environments.



MODEL RH

SPECIFICATIONS:

Voltage Options:	12 VDC, 24 VDC, 24 VAC, and 120 VAC
Sound Output Level	100dB @ 10'
Ratings:	UL Listed; CSA Approved
Operating Temp:	-65° F to 150° F (-54° C to 66° C)
Net Weight:	1.4 lbs. (.6 kg)
Shipping Weight:	1.5 lbs. (.7 kg)
Height:	4" (102 mm)
Width:	4" (102 mm)
Depth:	2.5" (64 mm)

ORDERING INFORMATION:

Part Number Designation –

“RH – VOLTAGE”

VOLTAGE: 12 VDC
24 VDC
24 VAC
120 VAC

OPTIONS –

WB – Optional cast aluminum neoprene – gasketed weatherproof housing for outside use, complete with mounting lugs; tapped for 1/2 “ conduit; 4 3/8” square box; 2” deep; 2 mounting lugs.